



PART NUMBER : 2MVTBK/S

**Normaled with 75 Ohm Termination
Micro Video Patch jack
Standard BNC rear Interface**

SPECIFICATIONS:

ELECTRICAL:

MEETS SMPTE 2082-1
CHARACTERISTIC IMPEDANCE: 75 OHMS
CONTACT RESISTANCE: LESS THAN 50 MILLIOHMS

MECHANICAL:

VIBRATION: PER MIL - STD 202, METHOD 201
INSERTION FORCE: 9 LBS MAX.
WITHDRAWAL FORCE: 2 LBS MIN.
LIFE CYCLE: 20,000 MIN.

MATERIAL:

HOUSING: COPPER ALLOY, NICKEL PLATED
CENTER CONTACTS: COPPER ALLOY, GOLD PLATED
SPRINGS: COPPER ALLOY, GOLD PLATED
INSULATORS: TEFLON AND THERMOPLASTIC

ENVIRONMENTAL:

TEMPERATURE
OPERATING: -40 °C TO 65 °C
STORAGE: -40 °C TO 65 °C

THERMAL SHOCK: PER MIL-STD- 202, METHOD 107
MOISTURE AND HUMIDITY: PER MIL-STD- 202, METHOD 106
SALT SPRAY: PER MIL-STD- 202, METHOD 101

THIS PRODUCT IS RoHS COMPLIANT.

